

RuggedAir100

WiFi access point, client, repeater & Mesh point designed for industrial applications in harsh environments



- All-in-one : AP/client/repeater/Mesh point
- WiFi 802.11n (MIMO 2T2R), 2.4/5 GHz
- Advanced security functions, VPN, firewall...
- WaveManager centralized management software
- Operating System : WaveOS
- Rugged device : shocks & vibrations proof, IP66, dual insulated redundant input +9VDC to +48VDC or PoE
- Fast roaming < 30 ms
- Compatible with its predecessor WLg-ABOARD



Introduction

As its predecessor (WLg-ABOARD) with which it is 100% compatible, RuggedAir100 is an "all-in-one" multifunction product (access point, client, repeater, router & Mesh point) designed for industrial applications in harsh environment (IP66 waterproof, shocks and vibrations proof, extended temperature range, M12 connectors...). It can be used either on the ground to create indoor or outdoor WiFi coverages, or on board to connect all types of mobile equipment or vehicles (trams, construction/agricultural machines, trucks, automated cranes, harbor cranes...) to the ground network.

- **Reliability** : it is equipped with a redundant wide range (9-48 VDC) or POE power supply as well as 2 antennas making it possible to reinforce the quality of the radio link and to increase the throughputs.
- **Mobility** : its roaming performances (<30 ms) and its shocks/vibrations resistance make it easy to integrate in any type of mobile equipment or vehicle.
- **Ease of deployment and maintenance** : RuggedAir100 can be easily managed from the network with the centralized management software WaveManager, through SNMP or from a simple web browser. It also has a C-Key (key saving configuration) for instant replacement on site.
- **Security** : it integrates advanced security standards (Firewall, VPN, 802.1X ...) as well as routing and filtering functions to facilitate mass deployments.

Technical characteristics overview

Ethernet interface	2-port Ethernet 10/100 auto-sensing, Base TX, auto MDI/MDIX, M12 D-coded Ethernet interface
WiFi interface	1 radio 802.11n (MIMO 2T2R, 300 Mbps), ANI (Adaptive Noise Immunity)
WiFi radio data rate	802.11a: 6, 9, 12, 18, 24, 36, 48 & 54 Mbps 802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 & 54 Mbps 802.11n: MCS0-7, 2 streams (6.5 to 300 Mbps)
Operating frequencies	ISM : 2.4-2.483 GHz (up to 14 channels) UNII : 5.15-5.25 GHz (up to 4 channels) UNII-2 : 5.25-5.35 GHz (up to 4 channels) UNII-2 ext : 5.470-5.725 GHz (up to 11 channels) UNII-3 : 5.725-5.825 GHz (up to 4 channels) Supports DFS and TPC
Output power	2,4 GHz : 23,5 dBm (aggregate) / 5 GHz : 21 dBm (aggregate)
Sensitivity max.	WiFi 802.11n receiver : -92 dBm for 802.11 b/g/n and -96 dBm for 802.11a/n
Radio connectors	2 N-type connectors
Security	Firewall, DoS, https, MAC filtering, WPA/WPA2-Personal & Enterprise (IEEE 802.1X/RADIUS), WEP, tunnels L2 (GRE), VPN (OpenVPN), SNMP V3
WiFi Modes	AP, client, MESH (IEEE 802.11s), infrastructure, AD-HOC, fast roaming (less than 30 ms), WMM QoS
Ethernet networking	Frames filtering, bridging, repeater, STP/RSTP, VLAN, DHCP (server & client), DNS relay
IP routing	Multicast (PIM), IP redundancy (VRRP), static routes, NAT router, router
Administration	http, https, SNMP agent (V1, V2C, V3), WaveManager administration software, save / restore configuration key (C-Key)
I/O	A 3-pin Waterproof M8 connector with : - one solid state relay output warning (with configurable action), 1 Form A, 60VDC 80mA max - one input for external device control 24VDC max
LEDs Signaling	Radio : activity - status Ethernet : link - activity Power : on-off C-Key : activity
Power supply	+9VDC to +48VDC, redundant, PoE af (at type 1), M12 connector 4-pole A-coded
Consumption	IDLE mode : 2.37 W / Maximum average : 3.92 W / Recommended : 5.70 W
Dimensions & weight	L : 175 x l : 80 x h : 75 mm (without connectors), weight TBD
Standards	CE (RED) & FCC (FCC ID : Z9W-RMB) certified Safety : EN45545-2 (HL3), NF F16-101 (M1F1) (Fire and Smoke), EN 62368-1:2014+A11, EN62311 Radio : EN 300 328 (2.4 GHz), EN 301 893 (5 GHz, DFS) CEM : partially compliant with EN 50155 / EN50121-3-2, EN 301 489 [-1], [-17] Environmental : EN61373 (shocks and vibration), EN60068 (climatic)
Environment	IP66 Operating : -40°C to +75°C , HR: 0-99%
Warranty	5 years

Ordering references

RuggedAir/1A	WiFi access point, client, repeater (WDS) & MESH point (802.11n), M12 Ethernet interface 10/100
Accessories	
WLg-M12U-ETH-2M	Ultra-Lock 4-point Ethernet cable, M12 to RJ45, 2 meters
WLg-M12U-ETH-5M	Ultra-Lock 4-point Ethernet cable, M12 to RJ45, 5 meters
WLg-M12U-ETH-10M	Ultra-Lock 4-point Ethernet cable, M12 to RJ45, 10 meters
WLg-M12U-PWR-2M	Ultra-Lock waterproof 4-point M12 power supply cable, 2 meters
WLg-M12U-PWR-5M	Ultra-Lock waterproof 4-point M12 power supply cable, 5 meters
WLg-M12U-PWR-10M	Ultra-Lock waterproof 4-point M12 power supply cable, 10 meters
C-Key_M1	Save / Restore configuration key
WL-ANT-2458/2-ONM	Dual band (2.4 / 5 Ghz) 2 dBi omni-directional antenna
WL-PLT-1	4-point fixing plate with ground lug

Toutes les marques citées sont des marques déposées. ACKSYS recherche continuellement l'amélioration de ses produits. Les présentes spécifications peuvent être modifiées sans préavis et les caractéristiques indiquées ne correspondent pas à des obligations contractuelles. Tous ces produits sont étudiés et fabriqués en France.

ACKSYS_RuggedAir100_US_RevA1_23/10/18