

1514BESD0LTE-04
Omnidirectional 4G antenna 4dBi
Order Number
1514-00071913-4G



Klantspecifieke standaardoplossingen
voor industriële automatisering

B.E.S.D. Benelux B.V.
Wilhelminahof 7 - 8, 5751 GJ Deurne
The Netherlands

T. +31 (0)493 316 554
M. +31 (0)6 154 75 370
E. info@besd.nl
i. www.besd.nl
KvK Eindhoven: 50025619

This GSM / UMTS / LTE antenna can be connected to a GSM / UMTS / LTE device with SMA interface, in order to send and receive signals.

| Specifications | |
|-------------------|------------------------------|
| Type of antenna | GSM / UMTS / LTE |
| Frequency range | 1710...1990MHz, 824...960MHz |
| Impedance | 50 Ohm |
| Polarization | Linear, vertical |
| V.S.W.R. | 4,0: 1 max |
| Gain / Frequency | 1,0-3,5dBi/790-960MHz |
| | 2,0-4,0dBi/1710-2170MHz |
| | 3,0-4,0dBi/2570-2620MHz |
| Connector | SMA male |
| Housing | ABS |
| Diameter | 21,60 mm max |
| Weight | 20 g |
| Length | 163,10 mm |
| Temperature range | -10°C to +55°C |

