



FIMP-XL-HYBRID

INDUSTRIAL COMPACT SPLICE BOX AND PATCH PANEL



FIMP-XL Hybrid combines two different worlds: Glass fiber and copper cables. It provides a high level of flexibility for your application since it has optical connectors for up to 12 fibers and 6 RJ45 connectors for network cables.

FIMP-XL Hybrid is ready for splicing and it already contains splice tray, couplings, pigtails and cable gland. Regarding different couplings, you can choose from SMA, ST, SC, LC, FC-PC, SC-RJ, E-2000 and E-2000 COMPACT. The front panel and the splice cassette can be removed for splicing and since the cassette is magnetizable, it can easily be fixed onto a splice unit. The cassette has got a hole for splice units with a bolt.

The powder coated stainless steel housing is also magnetizable so that the splice box can easily be affixed to another housing or to a switch cabinet in case of no different tray. Furthermore, FIMP-XL Hybrid has got a clip for DIN rail mounting (35mm) and a kit for wall fastening. Thus, there are space-saving and flexible solutions for mounting our FIMP-XL Hybrid.

Additionally fiber optic cables with MPO can be adapted by using FIMPO. And the optional cap protects your fiber and connectors.

The systems are built up modular. Customizing is possible by different assemblies, colors of the housing or logos.



Separable front panel

Type MM with 6 x RJ45 CAT 6	6xST Duplex 62MM	6xSC Duplex 62MM	3xLC Quattro 62MM	6xST Duplex 50MM	6xSC Duplex 50MM	3xLC Quattro 50MM			
Article no.	06200 0016 22169-00	06200 0016 22369-00	06200 0016 22439-00	06200 0016 12169-00	06200 0016 12369-00	06200 0016 12439-00			
Type SM with 6 x RJ45 CAT 6	6xST Duplex SM	6xSC Duplex SM	6xSC 8° APC Duplex SM	3xLC Quattro SM					
Article no.	06200 0016 36169-00	06200 0016 37069-00	06200 00163 38369-00	06200 0016 36439-00					

Kupplungen RJ 45

6 x RJ45, CAT 6a

Weight

860 g

Dimensions

Height: 138 mm; Width: 72 mm; Depth: 128 mm

Operating Temperature

-40 °C – +75 °C

Humidity

10% – 95% relative, non condensing

Housing

Stainless steel, powder coated

Accessories

Article no.

Description

0600E90001	Cable gland M20
0600E90002	Nut M20
0600E90003	Strain relief
0600E90007	Splice holder
0600E90008	Splice protection
0600E90009	Cable tie
0600E90010	Counter sunk screw
0600E90011	Screws
0600E90013	Dual Mount Kit
0600E90014	Lens tapping screw for Front panelbefestigung, Philipps screw, 2,2 x 9,5 mm