



RBMTX-Lite



B.E.S.D. Benelux BV
Tel. +31 (0)493 316 554
sales@besd.nl
www.besd.nl

Order number	RBMTX-Lite-4G	0512-1802132024-4G	•	Available
	RBMTX-Lite-4G-WiFi-BT	0512-1802132024-4G-WiFi-BT	○	Option
	RBMTX-Lite-4G-PIO	0512-1802132024-4G-PIO	-	Not available
	RBMTX-Lite-NB/CAT.M1/2G	0512-1802132024-NB/CAT.M1	•	Available with external converter
	RBMTX-Lite-4G-GPS	0512-1802132024-4G-GPS		

Network standard	GPRS	EDGE	UMTS	HSPA+	LTE (4G)	LTE Cat. NB1 Cat. NB1	LTE Cat. M1 Cat. M1
RBMTX-Lite-4G	•	•	•	•	•	-	-
RBMTX-Lite-4G-WiFi-BT	•	•	•	•	•	-	-
RBMTX-Lite-4G-PIO	•	•	•	•	•	-	-
RBMTX-Lite-NB/CAT.M1/2G	•	•	•	•	•	•	•
RBMTX-Lite-4G-GPS	•	•	•	•	•	-	-

Band	Dual	Quad
RBMTX-Lite-4G	-	•
RBMTX-Lite-4G-WiFi-BT	-	•
RBMTX-Lite-4G-PIO	-	•
RBMTX-Lite-NB/CAT.M1/2G	-	•
RBMTX-Lite-4G-GPS	-	•

GSM modem	RS232	USB
RBMTX-Lite-4G	•	•
RBMTX-Lite-4G-WiFi-BT	•	•
RBMTX-Lite-4G-PIO	•	•
RBMTX-Lite-NB/CAT.M1/2G	•	•
RBMTX-Lite-4G-GPS	•	•

Remote communication	RS232	RS485	LAN 10/100Mbps	WiFi	Bluetooth
RBMTX-Lite-4G	•	•	•	○	○
RBMTX-Lite-4G-WiFi-BT	•	•	•	•	•
RBMTX-Lite-4G-PIO	•	•	•	-	-
RBMTX-Lite-NB/CAT.M1/2G	•	•	•	○	○
RBMTX-Lite-4G-GPS	•	•	•	-	-

Operation	Inputs	Outputs	Analog inputs	Analog outputs
RBMTX-Lite-4G	-	-	-	-
RBMTX-Lite-4G-WiFi-BT	-	-	-	-
RBMTX-Lite-4G-PIO	•	•	-	-
RBMTX-Lite-NB/CAT.M1/2G	-	-	-	-
RBMTX-Lite-4G-GPS	-	-	-	-

Monitoring	I/O state	GPS location	Power supply ON	Temperature
RBMTX-Lite-4G	-	-	•	•
RBMTX-Lite-4G-WiFi-BT	-	-	•	•
RBMTX-Lite-4G-PIO	-	-	•	•
RBMTX-Lite-NB/CAT.M1/2G	-	-	•	•
RBMTX-Lite-4G-GPS	-	•	•	•

External memory	micro SD card
RBMTX-Lite-4G	•
RBMTX-Lite-4G-WiFi-BT	•
RBMTX-Lite-4G-PIO	•
RBMTX-Lite-NB/CAT.M1/2G	•
RBMTX-Lite-4G-GPS	•

Retrieving information from the interface and control	CAN	RS232	RS485	I2C	Modbus	M-Bus
RBMTX-Lite-4G	○	•	•	-	•	•
RBMTX-Lite-4G-WiFi-BT	○	•	•	-	•	•
RBMTX-Lite-4G-PIO	○	•	•	-	•	•
RBMTX-Lite-NB/CAT.M1/2G	○	•	•	-	•	•
RBMTX-Lite-4G-GPS	○	•	•	-	•	•

Control	SMS	E-mail	MMS	DataCall
RBMTX-Lite-4G	•	○	○	○
RBMTX-Lite-4G-WiFi-BT	•	•	○	○
RBMTX-Lite-4G-PIO	•	•	○	○
RBMTX-Lite-NB/CAT.M1/2G	•	•	○	○
RBMTX-Lite-4G-GPS	•	•	○	○

Programmable	Python	C	Java
RBMTX-Lite-4G	•	•	-
RBMTX-Lite-4G-WiFi-BT	•	•	-
RBMTX-Lite-4G-PIO	•	•	-
RBMTX-Lite-NB/CAT.M1/2G	•	•	-
RBMTX-Lite-4G-GPS	•	•	-

SIM card	Single	Dual
RBMTX-Lite-4G	-	•
RBMTX-Lite-4G-WiFi-BT	-	•
RBMTX-Lite-4G-PIO	-	•
RBMTX-Lite-NB/CAT.M1/2G	-	•
RBMTX-Lite-4G-GPS	-	•

Audio interface	○
-----------------	---

Power supply	9 - 30VDC
--------------	-----------

Dimensions	84 x 60 x 34mm
------------	----------------

Weight	110 gr
--------	--------